




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| | | |
|--|-----------|--|
| (51) International Patent Classification 6: A47J 36/26 | A1 | (11) International Publication Number: WO 97/47224 (43) International Publication Date: 18 December 1997 (18.12.97) |
| (21) International Application Number: PCT/GB97/01557 (22) International Filing Date: 10 June 1997 (10.06.97) (30) Priority Data: 9612234.6 12 June 1996 (12.06.96) GB (71)(72) Applicant and Inventor: PAUL, Claire, Cecilia [GB/GB]; East Harting Farmhouse, East Harting, Petersfield, Hamp- shire GU31 5LU (GB). (74) Agent: PRICE, Nigel, John, King; J.A. Kemp & Co., 14 South Square, Gray's Inn, London WC1R 5LX (GB). | | (81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report. |

(54) Title: IMPROVEMENTS IN AND RELATING TO FOOD PREPARATION

(57) Abstract

A food preparation device can be used for making up formula milk for a baby. The device includes a water tank (4) in which water may be boiled by operating a boil button (19). Once the boiled water has cooled down to a temperature below a predetermined temperature of approximately 45-55 °C, the previously boiled water may be reheated to said predetermined temperature by operating a button (20). Operating a button (20) causes water in the tank to be reheated to said predetermined temperature and to be discharged to a bottle (10) received in a bottle-receiving station (9). If dehydrated formula milk powder has previously been added to the bottle, once discharge is complete the bottle (10) may be capped with a teat, shaken to mix the powder with the water, and used to feed a baby or toddler.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | | | |
|----|--------------------------|----|--|----|--|----|--------------------------|
| AL | Albania | ES | Spain | LS | Lesotho | SI | Slovenia |
| AM | Armenia | FI | Finland | LT | Lithuania | SK | Slovakia |
| AT | Austria | FR | France | LU | Luxembourg | SN | Senegal |
| AU | Australia | GA | Gabon | LV | Latvia | SZ | Swaziland |
| AZ | Azerbaijan | GB | United Kingdom | MC | Monaco | TD | Chad |
| BA | Bosnia and Herzegovina | GE | Georgia | MD | Republic of Moldova | TG | Togo |
| BB | Barbados | GH | Ghana | MG | Madagascar | TJ | Tajikistan |
| BE | Belgium | GN | Guinea | MK | The former Yugoslav Republic of Macedonia | TM | Turkmenistan |
| BF | Burkina Faso | GR | Greece | | | TR | Turkey |
| BG | Bulgaria | HU | Hungary | ML | Mali | TT | Trinidad and Tobago |
| BJ | Benin | IE | Ireland | MN | Mongolia | UA | Ukraine |
| BR | Brazil | IL | Israel | MR | Mauritania | UG | Uganda |
| BY | Belarus | IS | Iceland | MW | Malawi | US | United States of America |
| CA | Canada | IT | Italy | MX | Mexico | UZ | Uzbekistan |
| CF | Central African Republic | JP | Japan | NE | Niger | VN | Viet Nam |
| CG | Congo | KE | Kenya | NL | Netherlands | YU | Yugoslavia |
| CH | Switzerland | KG | Kyrgyzstan | NO | Norway | ZW | Zimbabwe |
| CI | Côte d'Ivoire | KP | Democratic People's Republic of Korea | NZ | New Zealand | | |
| CM | Cameroon | | Republic of Korea | PL | Poland | | |
| CN | China | KR | Republic of Korea | PT | Portugal | | |
| CU | Cuba | KZ | Kazakstan | RO | Romania | | |
| CZ | Czech Republic | LC | Saint Lucia | RU | Russian Federation | | |
| DE | Germany | LI | Liechtenstein | SD | Sudan | | |
| DK | Denmark | LK | Sri Lanka | SE | Sweden | | |
| EE | Estonia | LR | Liberia | SG | Singapore | | |

- 1 -

IMPROVEMENTS IN AND RELATING TO FOOD PREPARATION

This invention relates to improvements in and relating to the preparation of food, including drinks and beverages. The invention has particular application to hot food and/or drink preparation devices particularly, but not exclusively, to devices for assisting in the preparation of a bottle of "formula" milk for a baby or toddler.

Formula milk for a baby or toddler requires boiled water to be added to formula milk powder. Boiled water must be used to ensure that the water is sterilized. However, at the time of mixing the sterilized water with the powder the water should not be boiling; instead it should be at a reduced temperature. Clearly, when the made-up formula milk is fed to the baby or toddler it must be at an appropriate feeding temperature well below boiling, suitably 45-55°C.

In making up a bottle of formula milk it is conventional to boil water in a kettle or pan to help to sterilize it, wait for it to cool to approximately 50°C and then add it to a baby feeding bottle. The formula milk powder may already have been placed in the bottle or else be added to the bottle following the addition of the hot, boiled water. Once the powder and water have mixed to form a bottle of formula milk the bottle may then be used to feed a baby or toddler, subject to it being cooled or heated to an appropriate feeding temperature if necessary. If, however, the bottle is being made in advance of being required, once it has cooled to room temperature it must be stored in a fridge and, when required, heated to an appropriate feeding temperature before being fed to the baby or toddler.

This procedure is not convenient. Furthermore, if a baby or toddler should wake during the night and require feeding, even if a bottle has been made up in advance it is necessary to retrieve it from the fridge and to monitor its

- 2 -

warming to an appropriate feeding temperature before the baby or toddler can be fed.

According to one aspect of the present invention there is provided a food preparation device comprising:

5 a water tank for holding water;

at least one bottle-receiving station for receiving a bottle which may contain dehydrated food preparation formulation and for the controlled discharge thereto from the tank of heated water;

10 first water heating means arranged to boil water in the tank;

second water heating means arranged to reheat to a predetermined maximum temperature below 100°C tank water which has previously been boiled in the tank and which has
15 then been allowed to cool to below said predetermined temperature;

selecting means for selecting operation of said water heating means either to boil tank water or to reheat it only to said predetermined temperature; and

20 regulating means for regulating the discharge of tank water from the tank to said at least one bottle-receiving station, said regulating means being arranged to permit the discharge of tank water reheated to said predetermined temperature.

25 Advantageously the first and second water heating means comprise a single heater positioned in the tank.

The device preferably comprises a plurality of bottle-receiving stations, each of which may have a bottle placed therein already containing an appropriate amount of
30 a powdered beverage formulation. The selecting means may include a first user-activatable switching means to permit a user to operate the heater to boil water contained in the tank. The selecting means also advantageously includes a plurality of second user-activatable switching means, one
35 for each bottle receiving station. By activating one or more of these second switching means the user can cause the

- 3 -

heater to heat the previously boiled water in the tank to the predetermined, reduced temperature (for example, 45-55°C) and to discharge the heated water at this reduced temperature to the bottle-receiving station or stations
5 associated with the second user-activatable switching means selected and activated by the user. In this way, if the device for example comprises six bottle-receiving stations and has six second user-activatable switching means, if the user activates only two of those second user-activatable
10 switching means, water at the reduced temperature can be discharged to bottles in two of the bottle-receiving stations only. In this way, a user can easily select the number of bottles of feed to be made up.

According to a second aspect of the present invention
15 there is provided a preparation device comprising:

means for providing a supply of liquid to be heated;

means for boiling the liquid supply; and

means for re-heating the previously boiled liquid to a reduced temperature; and

20 means for discharging the re-heated liquid at said reduced temperature to a receptacle;

wherein said device is operable, according to user choice, either (i) in a boiling mode to boil the liquid supply or (ii) to re-heat the previously boiled liquid to
25 said reduced temperature and to discharge it.

Embodiments of the invention will now be described, by way of example only, with reference to the accompanying drawings, in which:-

Fig. 1 shows, in perspective view, a first embodiment
30 of a device having six bottle-receiving stations;

Fig. 2 is a part-schematic, cross-sectional view along the longitudinal axis of the device of Fig. 1 and through two bottle-receiving stations, showing the bottles removed from the bottle-receiving stations and with teat-
35 covering lids removed.

Fig. 3 shows, in perspective view, a second

- 4 -

embodiment of a device in accordance with the present invention;

Fig. 4 is a part-schematic, cross-sectional view along the longitudinal axis of a third embodiment of a device in accordance with the present invention, showing the bottle-receiving stations and, in the base of the device, means for generating and supplying steam; and

Fig. 5 is a schematic, cross-sectional view along the line V-V in Fig. 4, with the bottles removed.

10 The first embodiment illustrated in Figs. 1 and 2 of the drawings comprises a base 1, a top 2 and a hollow, central column 3 therebetween. The top 2 contains a water tank 4 which contains a heater element 5. The top 2 and tank 4 are removable with the heater element 5 from the central column 3 so as to allow the tank to be emptied, cleaned and re-filled. The heater element 5 may be of a conventional plate (as shown) or coil construction such as is conventionally found in electric kettles. For ease of use, the tank 4 is provided with a removable lid 6. This also allows the tank 4 to be filled in-situ.

20 A releasable lock (not shown) may be provided to lock the top 2 to the column 3 to prevent its inadvertent removal.

In the first illustrated embodiment the water tank 4 is formed integrally with the top 2. Part of the top 2 may, however, be formed integrally with the column 3, and the tank 4 be removable from the interior of that part of the top 2.

25 The base 1, top 2 and column 3 may be made of any suitable material. The tank 4 (and the top 2) may, for example, be formed from a heat-resistant and easily cleanable material such as stainless steel or a plastics material and may be externally insulated to reduce the risk of burns.

35 The electrical supply to the heater 5 is via an electrical flex 7. A make-and-break electrical connector

- 5 -

8, of the sort conventionally used in cordless kettles and irons, is provided at the top of column 3 to provide power to the heater 5 whilst still allowing for the top 2 to be removable. The electrical elements visible inside the device in Figure 2 are shown schematically.

The first illustrated embodiment comprises six bottle-receiving stations 9. In Figure 1 three of these stations are visible and each of these three is shown as receiving a sterilized bottle 10. The bottle 10 may be a conventional baby/toddler feeding bottle suitable for containing an approximately 8 fluid ounce feed. To define each bottle-receiving station the base 1 of the device may, as shown, be provided with six recesses 11, each to receive the lower portion of a bottle 10.

In the first illustrated embodiment the top 2 is provided with air-tight sealing means 12 for sealing against the open, upper ends of bottles received in the stations 9. Each sealing means 12 comprises a generally annular cup-shaped element downwardly depending from the top 2 to seal against the upper shoulder of the bottle 10 received in the respective station 9. In this way the risk of contamination of a sterilized bottle 10 inserted into a station 9 can be reduced. The annular seal elements 12 may advantageously be made of resiliently flexible clear plastics material so as to allow the top of a bottle 10 to be inserted into its seal 12, pushed upwardly against the resilience of the seal to deflect the seal, and then to have its base swung inwardly and downwardly into the recess 11 for that station 9.

At each bottle-receiving station 9 a pipe 13 depends downwardly from the top 2 internally of and coaxially with the respective annular sealing element 12, to direct discharged water into the respective bottle 10, as will be explained below.

Advantageously, as shown, between each bottle-receiving station 9 there is shown an air-tight teat

- 6 -

storage station 14. Each teat storage station comprises an area of the base 1 and a cap 15 sealingly engaged with the base 1 to define therebetween a compartment for the storage therein of a sterilized teat, ring and cap 16, as shown.

5 The base area of each teat storage station may be recessed, as is most clearly shown in Figure 2. The cap 15 is removable from sealing engagement with the base to allow the extraction from the compartment of a teat, ring and cap. The air-tight sealing engagement between the caps 15
10 and the base 1 helps to reduce the risk of contamination of a sterilized teat 16 placed in the station compartment.

In the top 2 a thermostat 17 is exposed to the temperature of water contained in the tank 4. This thermostat 17 provides an input to a control means such as
15 a microprocessor controller 18, as shown schematically in Figure 2.

The top 2 is provided with selecting means for activating the heater 5. In the first illustrated embodiment the selecting means includes a first user-
20 activatable switching means, in the form of a button 19 which may be marked "BOIL" for allowing a user to activate the water heater 5 in a boil mode. This button 19 is connected to a microprocessor controller 18 by a connection (not shown). When button 19 is depressed by the user the
25 microprocessor controller 18 switches on the heater 5 to heat the water contained in the tank. When the thermostat 17 senses that the water temperature has reached boiling the microprocessor controller 18 cuts the power supply to the heater 5. The BOIL button 19 may be lit from behind
30 once the water in the tank has reached 100°C and the heater switched off so as to provide a visual indication to the user of the temperature of the water. The light behind the button may be arranged to switch off once the temperature of the water in the tank drops to a predetermined
35 temperature, for example 45-55°C. Advantageously, a safety cut out (not shown) may be provided to prevent the heater 5

- 7 -

from operating if the button 19 is depressed and the tank contains little or no water.

In the first illustrated embodiment the selecting means provided in the top 2 further includes a plurality of
5 second user-activatable switching means, each in the form of a switch 20. Each switch is connected to the microprocessor controller 18; two of the connections are shown schematically in Figure 2. Each bottle receiving station 9 is associated with a respective said switch 20;
10 only three such switches are visible in Figure 1.

Upon switching a switch 20 the microprocessor controller 18 advantageously senses the temperature of water in the tank 4 using the thermostat 17. If the water temperature is below a predetermined threshold temperature
15 (for example, 45-55°C) and there is sufficient water in the tank 4, the controller 18 switches on the heater 5 to increase the temperature of water in the tank 4 to that temperature. Once the water temperature reaches the threshold temperature the microprocessor controller 18 cuts
20 the power supply to the heater 5 and discharges heated water, at approximately the threshold temperature, to the bottle-receiving station or stations 9 associated with the switched switch or switches 20. If a switch 20 is switched and the BOIL button 19 has only recently been pressed such
25 that the tank water temperature is above the threshold temperature, heater 5 is not switched on, nor is any water discharged.

Discharge of water at approximately the threshold temperature is achieved by regulating means. In the first
30 illustrated embodiment these regulating means take the form of a plurality of automatically controlled electrically operated valves 21, one provided for each bottle-receiving station 9. Two such valves 21 are shown only schematically in Figure 2, as are their electrical connections to the
35 controller 18. Each valve 21 is selectively openable by the microprocessor controller 18 so as to allow the passage

- 8 -

of water from the tank 4 down the associated tube 13 to its respective bottle-receiving station 9. By opening a valve 21 for a predetermined time the amount of heated water discharged can be metered to an appropriate amount. In the case of a baby bottle, an average bottle size is approximately 8 fluid ounces.

As a non-illustrated alternative to the illustrated arrangement in which discharge of a metered amount of water takes place automatically upon the predetermined temperature being reached, the discharge may be controlled manually by the user following the heater 5 being switched off on the predetermined temperature being reached.

Ideally, the microprocessor control means 18 includes a safety feature whereby if the water temperature sensed by the thermostat 17 is greater than the threshold temperature under no circumstances can the valves 21 be opened to discharge water.

It will be appreciated that the preferred use of a microprocessor controller 18 to control operation of the heater 5 and valves 21 enables the ready achievement of safety features and also features which render the device more versatile. For example, the device may be provided with an override control (not shown) for enabling a user to stop the discharge of re-heated water to a bottle-receiving station before the normal, predetermined amount of re-heated water has been discharged, to enable a part-bottle feed to be prepared, and/or to prolong the discharge of re-heated water beyond said predetermined amount.

The first illustrated embodiment of the invention uses gravity to discharge heated water from the tank 4 to a bottle-receiving station 9. However, alternatively or additionally, pumping means may be provided. The pumping means may take the form of a pump of the type conventionally used in drinks vending machines, whereby the period of pump operation dictates the amount of fluid pumped.

- 9 -

In the above-described first embodiment, when a switch 20 is switched to activate the heater 5 to heat the water to the predetermined threshold temperature, the whole contents of the tank 4 are heated and only a portion thereof may be discharged. In an alternative arrangement (not shown), when a switch 20 is switched heating means separate from the heater 5 may be utilised. For example, the device may be provided with a syphon-type heater for each bottle-receiving station 9. Such heaters are commonly found in domestic filter coffee-making machines in which cold water from a reservoir is slowly admitted into a heating passage containing a one-way valve and the heating of the water is used to pump the water into a filter containing coffee-grounds. By using such a heater/pump in the device of the present invention one could avoid the need to heat all of the water to the threshold temperature, reducing the amount of time required to fill just one bottle with water of the correct temperature in the case where the tank 4 contains a large volume of water.

To help illustrate the features of the first illustrated embodiment of the invention, an exemplary procedure involving the device will now be described. In the following procedure the device is used to prepare a bottle of formula milk for a baby or toddler. The device is not, however, intended to be limited to this use alone or to use in accordance with the precise procedure described. It may, for example, be used in the preparation of drinks for adults, or for the preparation of foods for adults or children.

In an exemplary procedure the device is first prepared. Preparation will involve some or all of the bottle-receiving stations having sterilized bottles fitted therein. Prior to fitting them the sterilized bottles may have had an appropriate amount of powdered baby/toddler milk formulation added thereto.

Preparation will also involve checking that the tank

- 10 -

4 contains sufficient water. Ideally the tank 4 is removed from the remainder of the device and emptied of any residual water, and perhaps also cleaned. It can then either be filled and returned to the device containing
5 water, for example 40 fluid ounces of water (enough to make approximately 5 conventional 8 fluid ounce baby bottles) or replaced on the device empty and then filled through the aperture normally closed by the lid 6. The BOIL switch 19 is then pressed to cause the heater 5 to boil the whole
10 contents of the tank 4. The device may now be left. Once boiling of the water is detected via thermostat 17 the microprocessor controller 18 automatically switches off the power supply to the heater 5. The water contained in the tank 4 can then be allowed to cool. Over several hours it
15 will cool to approximately room temperature. The device is now in a prepared, ready-to-use condition.

Several hours later, when a baby or toddler is required to be fed, a switch 20 is switched. If two bottles of baby/toddler feed are required, two such
20 switches 20 are switched. Upon operation of one or more switches 20 the microprocessor controller 18 again activates heater 5. However, in contrast to when the BOIL switch 19 is pressed, once the water in the tank 4 has been heated to the predetermined, threshold temperature (in the
25 case of a baby bottle preparation device, approximately 45-55°C), the microprocessor controller 18 automatically cuts the supply of power to the heater 5 and opens the valves 21 of the bottle-receiving stations 9 whose switches 20 were switched. By opening the valves 21 for a predetermined
30 time period, or otherwise metering the amount of heated water discharged, approximately 8 fluid ounces of water at approximately the threshold temperature (45-55°C) is discharged into each of the sterilized bottles 10 present in the bottle-receiving stations 9 associated with the
35 selected and switched switches 20 only.

Once the appropriate amount of heated water has been

- 11 -

discharged (or discharge is extended or prematurely terminated using an override switch, as described above) each of the filled bottles 10 can be removed from the device by lifting the bottle upwardly to deflect the
5 respective resilient seal 12. If powdered baby/toddler milk formulation was added to the sterilized bottles prior to their being fitted to the device a sterile teat, ring and cap can be removed from a teat storage station and fitted to the removed bottle 10. Alternatively, if the
10 sterilized bottles 10 were placed empty in the bottle-receiving stations, an appropriate amount of baby/toddler milk powder can be added between removing a bottle from the device and fitting a sterile teat, ring and cap to the bottle. By then shaking the bottle 10 the heated water can
15 be caused to mix with the powdered beverage formulation present in the bottle, making the bottle ready for use. Several hours later the procedure of switching one or more switches 20, of stations still containing a bottle 10, may be repeated to obtain a further bottle or bottles of feed.

20 Due to the discharge of water from the tank 4, air will enter the tank during the discharge operation. A hole or one-way valve may, for example, be provided in lid 6 so as to admit air into the tank 4 in such a situation. To help to maintain as hygienic an environment in the tank as
25 possible it is suggested that following discharge of water from the tank, following switching of a switch 20, the BOIL switch 19 be pressed so as to cause the remaining water in the tank to be boiled again. This is not, however, essential.

30 Despite the above precaution it is suggested that the tank 4 should be emptied on at least a daily basis. Each time the tank is re-filled it is suggested that the BOIL switch 19 be switched so as to cause the water to be boiled to avoid the need to have to do this (and then to allow the
35 water to cool) when in due course it is required to prepare a bottle of feed.

- 12 -

So as to avoid the need for the device to meter the amount of water discharged it is envisaged that the tank 4 could be provided with internal partitions to partition the interior of the tank into a number of smaller reservoirs, each corresponding to a bottle-receiving station 9. In this way, an appropriate amount of water, for example eight fluid ounces, could be added to each reservoir so that, upon switching a switch 20, the valve 21 associated with the same station 9 can simply be open to admit all of the water contained in that station's reservoir.

As a further development of this idea, the tank 4 may be partitioned with internal weirs, again to divide the tank into a plurality of active reservoirs (one for each bottle-receiving station), together with a spare reservoir. In this way, when filling the tank 4 one could add water to the reservoir furthest away from the spare reservoir and allow the water successively to flow over the partitioning weirs so as to fill each of the active reservoirs with the correct amount of water.

In the Fig. 1 and 2 embodiment heating of the water to its reduced temperature (of approximately 45-55°C) is achieved by switching any switch 20. Discharge of the water at that reduced temperature takes place automatically once the reduced temperature has been reached. In a non-illustrated variant of this embodiment the selecting means includes a single REHEAT switch, switching of which allows a user to commence reheating of the water to the reduced temperature. Once this temperature is reached the heater 5 is automatically switched off and no heated water is discharged. In this variant the switches 20 are used not as selecting means to initiate operation of the heater, but as manually operable regulating means to enable a user to discharge water at the reduced temperature. If, for example, the valve 21 of a bottle-receiving station 9 is linked to that station's switch 20, by switching the switch 20 the valve 21 may be caused to open. If the valve 21 is

- 13 -

arranged to be directly controlled by the associated switch 20, by holding down the switch 4 for as long as a bottle takes to fill the switch can be used manually to meter out the required amount of water, avoiding the need for the device to be provided with automatic water discharge metering means.

Figure 3 shows a variant of the above-described devices. In the Fig. 3 variant the bottle-receiving stations are enclosed within a generally drum-shaped receptacle 50. This drum-shaped receptacle 50 may, as shown, advantageously be provided with a pair of doors 40, each provided with hinges 41 and a handle 42. When the doors 40 are closed, as shown in Figure 3, the receptacle so formed may advantageously be generally air-tight. When, in use, access is required to a bottle-receiving station to permit the insertion or removal therefrom of a bottle 10 the doors 14 may be swung open on their hinges 41 to provide access. As shown in Figure 3, in this variant caps for the teat storage stations 14 may be omitted due to the extra protection afforded by the receptacle.

Figures 4 and 5 illustrate a further variant of the Fig. 3 device. In Fig. 4 the top 2 of the device is omitted; it may be the same as in the earlier embodiments. In this further variant the base 1 of the device is provided with means for generating steam and supplying it to the interior of the enclosure or receptacle 50 enclosing the bottle-receiving stations 9. The steam generating and supplying means comprises an annular water tank 44 and heater plate 45 contained in the base of the tank 44. The heater plate 45 may be activated by a switch 46 provided on the base to boil water contained in the tank 44. In the illustrated embodiment the bases of the recesses 11 at the lower ends of the bottle-receiving stations 11 are formed from mesh to provide vents to the tank 44 to enable steam from the tank 44 to enter the interior of the receptacle 50. If, as shown, the bottles 10 received in the bottle-

- 14 -

receiving stations are inverted the steam will pass over as well as into the bottles 10. Similarly, the bases of the teat storage stations 14 may be formed of gauze to allow steam to wash over the items placed therein over the
5 central posts shown therein.

Activation and de-activation of the heater plate 45 may advantageously be provided by the microprocessor controller 18. Once the water in tank 44 has all been boiled off the heater plate 45 will be turned off by the
10 microprocessor controller.

To enable the steam generated to exit the device a steam exit hole 47 is provided in a wall of the receptacle 50.

As shown in Fig. 5, the top surface of the base 1 is
15 provided with an aperture 48 to allow water to be poured into the tank 44.

The on/off switch 46 is advantageously back-lit when the heater plate 45 is in operation.

Following activation of the steam generating and
20 supplying means, once the bottles 10 have cooled sufficiently they may be removed from the bottle-receiving stations 9, charged with an appropriate amount of baby milk formulation and replaced in the bottle-receiving stations 9 in their upright positions as shown in Figs. 1-3.
25 Subsequent operation of the device is, for example, as described above in relation to the earlier embodiments.

The further variant of Figs. 4 and 5 thus additionally has the means to sterilise bottles. The bottles may thus be sterilised using the steam generating
30 and supplying means and then the water in the top tank 4 boiled, as a two-stage process to prepare the device, prior to it being needed to prepare food.

Although the device is illustrated as having six bottle-receiving stations the invention is applicable to
35 devices having as few as one bottle-receiving station.

- 15 -

CLAIMS

1. A food preparation device comprising:
a water tank for holding water;
5 at least one bottle-receiving station for receiving a bottle which may contain dehydrated food preparation formulation and for the controlled discharge thereto from the tank of heated water;
first water heating means arranged to boil water in
10 the tank;
second water heating means arranged to reheat to a predetermined maximum temperature below 100°C tank water which has previously been boiled in the tank and which has then been allowed to cool to below said predetermined
15 temperature;
selecting means for selecting operation of said water heating means either to boil tank water or to reheat it only to said predetermined temperature; and
regulating means for regulating the discharge of tank
20 water from the tank to said at least one bottle-receiving station, said regulating means being arranged to permit the discharge of tank water reheated to said predetermined temperature.
2. A device as claimed in claim 1, wherein the
25 regulating means is arranged not to permit the discharge to said at least one bottle-receiving station of tank water above said predetermined temperature.
3. A device as claimed in claim 1 or claim 2,
wherein the first and second water heating means are the
30 same.
4. A device as claimed in claim 3, wherein the first and second water heating means comprise a single heater positioned in the tank.
5. A device as claimed in any one of the preceding
35 claims, wherein said predetermined temperature is approximately 45°C - 55°C.

- 16 -

6. A device as claimed in any one of the preceding claims, further comprising control means for automatically deactivating said water heating means when the temperature of water in the tank reaches boiling, following activation
5 of said water heating means by a user selecting operation of the water heating means to boil the water.

7. A device as claimed in claim 6, wherein the control means is also arranged to automatically deactivate said water heating means when the temperature of water in
10 the tank reaches said predetermined temperature following activation of the water heating means by a user selecting operation of the water heating means to re-heat the previously boiled water to said predetermined temperature.

8. A device as claimed in any one of the preceding
15 claims, wherein the regulating means includes a valve.

9. A device as claimed in claim 8 wherein, when there are a plurality of bottle-receiving stations, a said valve is provided for each bottle-receiving station for regulating the discharge of water at said predetermined
20 temperature to its respective bottle-receiving station.

10. A device as claimed in any one of the preceding claims, wherein said regulating means is arranged to regulate automatically the discharge to said at least one bottle-receiving station of a predetermined amount of water
25 heated to said predetermined temperature.

11. A device as claimed in claim 10, wherein the regulating means further includes an override to allow a user to terminate prematurely or to extend the discharge of heated water so as to change the amount of heated water
30 discharged from the predetermined amount.

12. A device as claimed in claim 10 or claim 11, wherein the regulating means includes a metering unit for metering said predetermined amount of heated water, said predetermined amount being less than the full capacity of
35 the tank.

13. A device as claimed in any one of the preceding

- 17 -

claims, wherein said selecting means includes a first user-activatable switching means to allow a user to activate the first water heating means to boil water in the tank.

14. A device as claimed in claim 13, wherein said
5 selecting means includes a second user-activatable switching means to allow a user to activate the second water heating means to heat water in the tank to said predetermined temperature only.

15. A device as claimed in claim 14 wherein, when
10 there are a plurality of bottle-receiving stations, said selecting means includes a separate said second user-activatable switching means for each bottle-receiving station to allow the user to select one or more said stations by switching the respective switching means and
15 thereby to activate the second water heating means prior to the automatic discharge of water at said predetermined temperature only to the bottle-receiving station or stations corresponding to user-selected and switched said second switching means.

20 16. A device as claimed in claim 15 wherein, when there are a plurality of bottle-receiving stations, the second user-activatable switching means for each said station is provided on the device adjacent to its respective bottle-receiving station.

25 17. A device as claimed in any one of claims 1 to 9 and, when not appendant to any of claims 10 to 12, either of claims 13 and 14, wherein the regulating means is manually operable whereby, following heating of the water to said predetermined temperature, the amount of water
30 discharged is manually regulated by a user.

18. A device as claimed in claim 17 wherein, when there are a plurality of bottle receiving stations, a separate switching means is provided for each said station to allow a user manually to regulate the discharge of
35 heated water at said predetermined temperature.

19. A device as claimed in any one of the preceding

- 18 -

claims, further comprising control means for controlling operation of the second heating means and for controlling operation of the regulating means whereby, during operation of the second heating means, the second heating means is
5 deactivated when the water temperature reaches said predetermined temperature and the regulating means is then operable to allow water at said predetermined temperature to be discharged only to a user-selected bottle-receiving station or stations.

10 20. A device as claimed in claim 19, wherein said control means is arranged to prevent operation of the second water heating means when the temperature of water in the tank is already at or over said predetermined temperature.

15 21. A device as claimed in claim 19 or claim 20, wherein said control means includes a thermostat exposed to the temperature of water in the tank.

 22. A device as claimed in any one of claims 19-21, wherein said control means includes a microprocessor.

20 23. A device as claimed in any one of the preceding claims, wherein the device includes a top and the bottle-receiving station or stations is/are located underneath the top.

 24. A device as claimed in claim 23, wherein the
25 tank is provided in the top.

 25. A device as claimed in claim 24, wherein the tank is removable from the device.

 26. A device as claimed in claim 25, wherein the removable tank is provided with a make-and-break electrical
30 connector for the supply of electrical power to the heating means.

 27. A device as claimed in any one of claims 23-26, wherein the top is provided with sealing means for sealing against an open upper end of a bottle received in said at
35 least one bottle-receiving station.

 28. A device as claimed in claim 27, wherein the

- 19 -

sealing means comprises a downwardly depending generally annular element arranged to seal against an upper portion of the received bottle.

29. A device as claimed in claim 28, wherein a pipe
5 depends downwardly from the top, internally of and coaxially with the generally annular element, to direct discharged water into the received bottle.

30. A device as claimed in any one of the preceding claims, wherein the device includes a base upon which, in
10 use, a bottle received in the or each bottle-receiving station rests.

31. A device as claimed in claim 30, wherein the base is indented to receive and locate a lower portion of a received bottle.

15 32. A device as claimed in claim 30 or 31, wherein the base is provided with a teat storage station.

33. A device as claimed in claim 32, wherein the teat storage station comprises an area of the base and a cap sealingly engageable with the base to define with said
20 area of the base a compartment for the storage therein of at least one sterilized teat, the cap being removable from sealing engagement with the base to allow the extraction therefrom of a sterilized teat.

34. A device as claimed in claim 32 or 33, wherein
25 a plurality of bottle storage stations are provided and a separate teat storage station is provided for each bottle-receiving station.

35 35. A device as claimed in any one of the preceding claims in combination with a bottle, said bottle being
30 received in said at least one bottle receiving station.

36. A device as claimed in any one of the preceding claims, wherein the device further comprises an enclosure substantially enclosing said at least one bottle-receiving station and any bottle received therein.

37. A device as claimed in claim 36, wherein the
35 device further comprises a selectively operable steam

- 20 -

generator for generating steam and supplying it to the interior of the enclosure.

38. A device as claimed in claim 37, wherein the steam generator is arranged to direct steam into the interior of a received bottle enclosed in the enclosure.

39. A device as claimed in claim 37 or claim 38, wherein the device has a base and the steam generator is provided in the base to direct steam into an inverted bottle received in said at least one bottle receiving station via an aperture provided in the base.

40. A device as claimed in claim 39, wherein at least one element extends across the aperture to support the inverted bottle whilst also allowing for the passage of steam through the aperture.

41. A device as claimed in claim 39 or claim 40, wherein the steam generator comprises a water receptacle and heater in the base.

42. A device as claimed in any one of claims 36 to 41, wherein the enclosure is provided with at least one openable and closable door to allow for removal and replacement of a bottle in said at least one bottle-receiving station.

43. A device as claimed in any one of claims 36 to 42, wherein the enclosure is vented to allow for the exit of steam from the housing.

44. A preparation device comprising:
means for providing a supply of liquid to be heated;
means for boiling the liquid supply; and
means for re-heating the previously boiled liquid to a reduced temperature; and

means for discharging the re-heated liquid at said reduced temperature to a receptacle;

wherein said device is operable, according to user choice, either (i) in a boiling mode to boil the liquid supply or (ii) to re-heat the previously boiled liquid to said reduced temperature and to discharge it.


- 21 -

45. A device as claimed in claim 44, wherein the discharging means is adapted automatically to discharge some or all of the previously boiled liquid upon it being re-heated to said reduced temperature by the re-heating
5 means.

46. A device as claimed in claim 44, wherein the discharging means is manually operable whereby, following the re-heating of the previously boiled liquid to said reduced temperature by the re-heating means, a user of the
10 device may operate the discharge means to control the amount of re-heated water to be discharged.


1/4

Fig.1.



2/4

Fig.2.



3/4

Fig.3.




Fig.4.





Fig.5.



INTERNATIONAL SEARCH REPORT

Int. Application No
PCT/GB 97/01557

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A47J36/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 A47J A61J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|--|---------------------------------------|
| A | GB 2 240 465 A (MC ARDLE) 7 August 1991 see page 7, last paragraph - page 33, paragraph 2; figures 1,2,7,12 --- | 1-8,10, 20-22, 44,45 |
| A | DE 35 11 159 A (BASE TEN SYSTEMS ELECTRONICS GMBH) 9 October 1986 see page 10, paragraph 2 - page 23, paragraph 1; figures --- | 1-10,12, 21-25, 30,31, 44,45 |
| A | WO 93 18695 A (HELD) 30 September 1993 see page 4, paragraph 3 - page 6, paragraph 3; figures 1,5 --- -/- | 1-8,10, 21,37, 38,40,44 |

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

10 September 1997

Date of mailing of the international search report

24.09.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

Bodart, P

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/GB 97/01557

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|---|-----------------------|
| A | WO 89 02239 A (SERAM) 23 March 1989 see page 3, line 11 - page 6, line 19; figures --- | 1,44 |
| A | DE 31 10 060 A (DEVAPPA) 4 November 1982 see page 4, paragraph 2 - page 9, paragraph 1; figures --- | 23,27, 30,35-37 |
| A | US 4 560 455 A (PORTA ET AL) 24 December 1985 see column 3, line 35 - column 4, line 16; figure 1 ----- | 38-40 |

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. Application No

PCT/GB 97/01557

| Patent document cited in search report | Publication date | Patent family member(s) | Publication date |
|---|---------------------|---|--|
| GB 2240465 A | 07-08-91 | NONE | |
| DE 3511159 A | 09-10-86 | NONE | |
| WO 9318695 A | 30-09-93 | DE 4208431 C EP 0636007 A | 23-09-93 01-02-95 |
| WO 8902239 A | 23-03-89 | FR 2620017 A | 10-03-89 |
| DE 3110060 A | 04-11-82 | DE 3010889 A AT 7452 T EP 0036612 A | 01-10-81 15-06-84 30-09-81 |
| US 4560455 A | 24-12-85 | CH 651211 A AU 562903 B AU 2495484 A CA 1215210 A WO 8403045 A EP 0115893 A JP 60500405 T | 13-09-85 18-06-87 30-08-84 16-12-86 16-08-84 15-08-84 28-03-85 |

THIS PAGE BLANK (USPTO)

